



Single Monitor Arm Comparison Chart



Zilker Single Monitor Arm

Crestview Single Monitor Arm

Range Single Monitor Arm

Moontower Single Monitor Arm

Enfield Single Monitor Arm

MON001

MON031

MON020

MON051

MON041



15 year warranty

15 year warranty

15 year warranty

15 year warranty

15 year warranty

Slim, attractive design

USB Kit add-on option
Compatible with a large range of monitors

Long reach
Compatible with a large range of monitors

Simple, economic

Elegant, modern design with spring tension indicator

Weight capacity: 4.4 to 11 lb

Weight capacity: 2.2 to 33 lb

Weight capacity: 4.5 to 17.5 lb

Weight capacity: 17.6 lb

Weight capacity: 4.4 to 19.8 lb

Supports any monitor size within weight range*

Supports any monitor size within weight range*

Supports any monitor size within weight range*

Supports any monitor size within weight range*

Supports any monitor size within weight range*

Clamp mount:
Compatible with 0.75" to 3.75" thick desktops

Clamp mount:
Compatible with 0.4" to 3.3" thick desktops

Clamp mount:
Compatible with 0.75" to 3.75" thick desktops

Clamp mount:
Compatible with 0.4" to 3.4" thick desktops

Clamp mount:
Compatible with 0.4" to 3.3" thick desktops

Bolt-through mount:
Compatible with 0.6" to 2.13" thick desktops

Bolt-through mount:
Compatible with 0.4 to 1.8" thick desktops

Bolt-through mount:
Compatible with 0.6" to 2.13" thick desktops

Bolt-through mount:
Compatible with 0.4" to 3.4" thick desktops

Bolt-through mount:
Compatible with 0.4 to 3.1" thick desktops

VESA compatibility:
75mm and 100mm
Quick release

VESA compatibility:
75mm and 100mm
Quick release

VESA compatibility:
75mm and 100mm
Quick release

VESA compatibility:
75mm and 100mm

VESA Compatibility:
75mm and 100mm
Quick Release

Clamp or bolt-through mount (both included)

Clamp or bolt-through mount (both included)

Clamp or bolt-through mount (both included)

Clamp or bolt-through mount (both included)

Clamp or bolt-through mount (both included)

Mechanical spring

Gas spring

Gas spring

Pole mounted

Mechanical spring

Height range: 6.75" to 19" **

Height range: 10" to 23" **

Height range: 4.25" to 18.75" **

Height range: 2.8" to 16.9" **

Height range: 8.7" to 18.5" **

12.25" vertical height adjustment

13" vertical height adjustment

14.5" vertical height adjustment

14.1" vertical height adjustment

9.8" vertical height adjustment

20" max forward reach ***

23.5" max forward reach ***

26.64" max forward reach ***

17" max forward reach ***

21.1" max forward reach ***

Side extension: 18.5" ****

Side extension: 20.7" ****

Side extension: 23" ****

Side extension: 14.4" ****

Side extension: 18.3" ****

Collapses down to 3.6"

Collapses down to 4.6"

Collapses down to 4.5"

Collapse down to 6.75"

Collapse down to 4.6"

Swivel of arm at base: 360°, 180°

Swivel of arm at base: 360°, 180°

Swivel of arm at base: 360°, 180°

Swivel of arm at base: 180°

Swivel of arm at base: 360°, 180°

Monitor tilt range: 60° (+/-30°)

Monitor tilt range: 90° (+/-45°)

Monitor tilt range: 160° (+90°/-70°)

Monitor tilt range: 90° (+/- 45°)

Monitor tilt range: 80° (+/- 40°)

Monitor pan range: 180° (+/-90°)

Monitor pan range: 180° (+/-90°)

Monitor pan range: 180° (+/-90°)

Monitor pan range: 180° (+/-90°)

Monitor pan range: 180° (+/-90°)

Monitor rotation: 360°

Monitor rotation: 180° (+/-90°)

Monitor rotation: 360°

Monitor rotation: 360°

Monitor rotation: 360°

Packaging dimensions: 17.3" x 9.25" x 4.3"

Packaging dimensions: 22.1" x 10" x 4.3"

Packaging dimensions: 19.06" x 12.95" x 5.91"

Packaging dimensions: 19.4" x 7.6" x 5.9"

Packaging dimensions: 17.5" x 9.4" x 5"

Weighs 6 lb with clamp, 4 lb 12 oz with bolt-through

Weighs 11.2 lb with clamp, 9.1 lb with bolt-through

Weighs 9 lb 14 oz with clamp, 8 lb 10 oz with bolt-through

Weighs 7.8 lb with clamp, 6.5 lb with bolt-through

Weighs 6 lb with clamp, 5.25 lb with bolt-through

Bolt hole diameter: 0.4" to 3.2"

Bolt hole diameter: 0.4" to 3.1"

Bolt hole diameter: 0.4" to 3.2"

Bolt hole diameter: 0.4" to 3.1"

Bolt hole diameter: 0.4" to 3.1"


* With monitor at back of desk, max monitor width will decrease as the arms are pulled forward

** Height range measured from desk surface to center of monitor mount

*** Max forward reach measured from center of post to VESA plate

**** Side extension is how far the monitor arm can extend out to the left or right. It is measured from the center of the post/base to the center of the VESA plate

Dual Monitor Arm Comparison Chart

					
Zilker Dual Monitor Arm	Range Dual Monitor Arm	Crestview Dual Monitor Arm	Crestview Align Dual Monitor Arm	Moontower Dual Monitor Arm	Enfield Dual Monitor Arm
MON002	MON021	MON032	MON033	MON052	MON042
					
15 year warranty	15 year warranty	15 year warranty	15 year warranty	15 year warranty	15 year warranty
Slim, attractive design	Dual long reach	USB Kit add-on option Holds lighter/heavier monitors	USB Kit add-on option Move and keep monitors in line with one motion	Simple, economic	Elegant, modern design with spring tension indicator
Weight capacity: 4.4 to 11 lb per arm	Weight capacity: 4.5 to 17.5 lb per arm	Weight capacity: 2.2 to 33 lb per arm	Weight capacity: 2.2 to 17.6 lb per arm	Weight capacity: 17.6 lb per arm	Weight capacity: 4.4 to 19.8 lb per arm
39.5" Max Monitor Size*	52" Max Monitor Size*	35" Max Monitor Size*	32" Max Monitor Size*	27" Max Monitor Size*	32" Max Monitor Size*
Clamp mount: Compatible with 0.75" to 3.75" thick desktops	Clamp mount: Compatible with 0.75" to 3.75" thick desktops	Clamp mount: Compatible with 0.4" to 3.3" thick desktops	Compatible with Compatible with 0.4" to 3.3" thick desktops	Clamp mount: Compatible with 0.4" to 3.4" thick desktops	Clamp Mount: Compatible with 0.4" to 3.3" thick desktops
Bolt-through mount: Compatible with 0.6" to 2.13" thick desktops	Bolt-through mount: Compatible with 0.6" to 2.13" thick desktops	Bolt-through mount: Compatible with 0.4 to 1.8" thick desktops	Bolt-through mount: Compatible with 0.4 to 1.8" thick desktops	Bolt-through mount: Compatible with 0.4 to 3.4" thick desktops	Bolt-Through Mount: Compatible with 0.4 to 3.1" thick desktops
VESA compatibility: 75mm and 100mm Quick release	VESA compatibility: 75mm and 100mm Quick release	VESA compatibility: 75mm and 100mm Quick release	VESA compatibility: 75mm and 100mm Quick release	VESA Compatibility: 75mm and 100mm	VESA compatibility: 75mm and 100mm Quick release
Clamp or bolt-through mount (both included)	Clamp or bolt-through mount (both included)	Clamp or bolt-through mount (both included)	Clamp or bolt-through mount (both included)	Clamp or bolt-through mount (both included)	Clamp or bolt-through mount (both included)
Mechanical spring	Gas spring	Gas spring	Gas spring	Pole mounted	Mechanical spring
Height range: 6.75" to 19" **	Height range: 4.75" to 21" **	Height range: 10" to 23" **	Height Range: 10.4" to 23.4" **	Height range: 2.8" to 16.9" **	Height range: 8.7" to 18.5" **
12.25" vertical height adjustment	16.25" vertical height adjustment	13" vertical height adjustment	13" vertical height adjustment	14.1" vertical height adjustment	9.8" vertical height adjustment
20.5" max forward reach***	26.6" max forward reach***	23.5" max forward reach***	24.8" max forward reach***	17.6" max forward reach***	21.1" max forward reach***
Side extension: 19.75" ****	Side extension: 26" ****	Side extension: 22.2" ****	Side extension: 35.8" ****	Side extension: 14.4" ***	Side extension: 20" ****
Collapses down to 3.6"	Collapses down to 4.5"	Collapses down to 4.6"	Collapses down to 5.25" (9.25" with handle)	Collapses down to 6"	Collapse down to 4.6"
Swivel of arm at base: 360°, 180°	Swivel of arm at base: 360°, 180°	Up to 270 degrees swivel per arm	Swivel of arm at base: 360°, 180°	Swivel of arm at base: 180°	Swivel of arm at base: 360°, 180°
Monitor tilt range: 60° (+/-30°)	Monitor tilt range: 160° (+90°/-70°)	Monitor tilt range: 90° (+/-45°)	Monitor tilt range: 20° (+/-10°)	Monitor tilt range: 90° (+/- 45°)	Monitor tilt range: 80° (+/- 40°)
Monitor pan range: 180° (+/-90°)	Monitor pan range: 180° (+/-90°)	Monitor pan range: 180° (+/-90°)	Monitor pan range: 20° (+/-10°)	Monitor pan range: 180° (+/-90°)	Monitor pan range: 180° (+/-90°)
Monitor rotation: 360°	Monitor rotation: 360°	Monitor rotation: 180° (+/-90°)	Monitor rotation: 360°	Monitor rotation: 360°	Monitor rotation: 360°
Packaging dimensions: 17.1" x 12.4" x 5.4	Packaging dimensions: 23.1" x 14.1" x 5.9"	Packaging dimensions: 25.4" x 14" x 4.7"	Packaging dimensions: 35.2" x 8.9" x 5.9"	Packaging dimensions: 27.1" x 7.6" x 5.9"	Packaging dimensions: 17.5" x 13.2" x 5"
Weighs 9.8 lb with clamp, 8.6 lb with bolt-through	Weighs 20.5 lbs with clamp, 17.9 lb with bolt-through	Weighs 18.1 lb with clamp, 16.1 lb with bolt-through	Weighs 18.1 lb with clamp, 16.1 lb with bolt-through	Weighs 10.2 lb with clamp, 9 lb with bolt-through	Weighs 9.5 lb with clamp, 8.5 lb with bolt-through
Bolt hole diameter: 0.4" to 3.2"	Bolt hole diameter: 0.4" to 3.2"	Bolt hole diameter: One hole: 2.2" to 3.1" Two holes: .4" to 1.3" each, spaced 1.7" apart"	Bolt hole diameter: 0.4" to 3.1"	Bolt hole diameter: 0.4" to 3.1"	Bolt hole diameter: 0.4" to 3.1"

* With monitor at back of desk, max monitor width will decrease as the arms are pulled forward

** Height range measured from desk surface to center of monitor mount

*** Max forward reach measured from center of post to VESA plate

**** Side extension is how far the monitor arm can extend out to the left or right. It is measured from the center of the post/base to the center of the VESA plate

Triple, Quad, and Six Monitor Arm Comparison Chart




Crestview Align Triple Monitor Arm



Moontower Triple Monitor Arm



Moontower Quad Monitor Arm



Moontower Six Monitor Arm

MON034	MON053	MON054	MON056
15 year warranty	15 year warranty	15 year warranty	15 year warranty
USB Kit add-on option Move and keep monitors in line with one motion	Simple, economic	Simple, economic	Simple, economic
Weight capacity: 2.2 to 13.2 lb per arm	Weight capacity: 17.6 lb per arm	Weight capacity: 17.6 lb per arm	Weight capacity: 14.3 lb per arm
27" Max Monitor Size*	27" Max Monitor Size*	27" Max Monitor Size*	27" Max Monitor Size*
Clamp mount: Compatible with 0.4" to 3.3" thick desktops Bolt-through mount: Compatible with 0.4 to 1.8" thick desktops	Compatible with 0.4" to 3.4" thick desktops	Compatible with 0.4" to 3.4" thick desktops	Compatible with 0.4" to 3.4" thick desktops
VESA Compatibility: 75mm and 100mm Quick Release	VESA Compatibility: 75mm and 100mm	VESA Compatibility: 75mm and 100mm	VESA Compatibility: 75mm and 100mm
Clamp or bolt-through Mount (both included)	Clamp or bolt-through Mount (both included)	Clamp or bolt-through Mount (both included)	Clamp or bolt-through Mount (both included)
Gas Spring	Pole Mounted	Pole Mounted	Pole Mounted
Height Range: 10.4" to 23.4" **	Height Range: 2.8" to 16.9" **	Height Range: 2.8" to 29.1" **	Height Range: 2.8" to 29.1" **
13" vertical height adjustment	14.1" vertical height adjustment	26.3" vertical height adjustment	26.3" vertical height adjustment
24.8" max forward reach***	29.5" max forward reach***	17.6" max forward reach***	29.5" max forward reach***
Side extension: 47.5" ****	Side extension: 26.3" ****	Side extension: 14.4" ****	Side extension: 26.3" ****
Collapses down to 5.25" (9.25" with handle)	Collapses down to 6"	Collapses down to 6"	Collapses down to 6"
Swivel of arm at base: 360°, 180°	Swivel of arm at base: 180°	Swivel of arm at base: 180°	Swivel of arm at base: 180°
Monitor tilt range: 20° (+/-10°)	Monitor tilt range: 90° (+/- 45°)	Monitor tilt range: 90° (+/- 45°)	Monitor tilt range: 90° (+/- 45°)
Monitor pan range: 20° (+/-10°)	Monitor pan range: 180° (+/-90°)	Monitor pan range: 180° (+/-90°)	Monitor pan range: 180° (+/-90°)
Monitor rotation: 360°	Monitor rotation: 360°	Monitor rotation: 360°	Monitor rotation: 360°
Packaging dimensions: 24.5" x 12.6" x 5.7"	Packaging dimensions: 32.4" x 7.6" x 5.9"	Packaging dimensions: 31.2" x 11.1" x 5.9"	Packaging dimensions: 31" x 14" x 5.9"
Weighs 18 lb with clamp, 15.9 lb with bolt-through	Weighs 13.6 lb with clamp, 12.4 lb with bolt-through	Weighs 17.1 lb with clamp, 15.9 lb with bolt-through	-Weighs 24 lb with clamp, 22.8 lb with bolt-through
Bolt hole diameter: 0.4" to 3.1"	Bolt hole diameter: 0.4" to 3.1"	Bolt hole diameter: 0.4" to 3.1"	Bolt hole diameter: 0.4" to 3.1"



* With monitor at back of desk, max monitor width will decrease as the arms are pulled forward

** Height range measured from desk surface to center of monitor mount

*** Max forward reach measured from center of post to VESA plate

**** Side extension is how far the monitor arm can extend out to the left or right. It is measured from the center of the post/base to the center of the VESA plate

Moontower Monitor Arm Comparison Chart



Moontower Single Monitor Arm

Moontower Dual Monitor Arm

Moontower Triple Monitor Arm

Moontower Quad Monitor Arm

Moontower Six Monitor Arm

MON051

MON052

MON053

MON054

MON056



15 year warranty

15 year warranty

15 year warranty

15 year warranty

15 year warranty

Simple, Economic

Simple, economic

Simple, economic

Simple, economic

Simple, economic

Weight capacity: 17.6 lb

Weight capacity: 17.6 lb per arm

Weight capacity: 17.6 lb per arm

Weight capacity: 17.6 lb per arm

Weight capacity: 14.3 lb per arm

Supports any monitor size within weight range

27" Max Monitor Size*

27" Max Monitor Size*

27" Max Monitor Size*

27" Max Monitor Size*

Compatible with 0.4" to 3.4" thick desktops

Compatible with 0.4" to 3.4" thick desktops

Compatible with 0.4" to 3.4" thick desktops

Compatible with 0.4" to 3.4" thick desktops

Compatible with 0.4" to 3.4" thick desktops

VESA compatibility: 75mm and 100mm

VESA Compatibility: 75mm and 100mm

VESA Compatibility: 75mm and 100mm

VESA Compatibility: 75mm and 100mm

VESA Compatibility: 75mm and 100mm

Clamp or bolt-through mount (both included)

Clamp or bolt-through mount (both included)

Clamp or bolt-through mount (both included)

Clamp or bolt-through mount (both included)

Clamp or bolt-through mount (both included)

Pole mounted

Pole mounted

Pole Mounted

Pole Mounted

Pole Mounted

Height Range: 2.8" to 16.9"

Height Range: 2.8" to 16.9"
**

Height Range: 2.8" to 16.9"
**

Height Range: 2.8" to 29.1"
**

Height Range: 2.8" to 29.1"
**

14.1" vertical height adjustment

14.1" vertical height adjustment

14.1" vertical height adjustment

26.3" vertical height adjustment

26.3" vertical height adjustment

Max forward reach: 17"***

Max forward reach: 17.6"***

Max forward reach: 29.5"***

Max forward reach: 17.6"***

Max forward reach: 29.5"***

Side extension: 14.4"****

Side extension: 14.4"***

Side extension: 26.3"****

Side extension: 14.4"****

Side extension: 26.3"****

Collapse down to 6.75"

Collapses down to 6"

Collapses down to 6"

Collapses down to 6"

Collapses down to 6"

Swivel of arm at base: 360°, 180°

Swivel of arm at base: 180°

Swivel of arm at base: 180°

Swivel of arm at base: 180°

Swivel of arm at base: 180°

Monitor tilt range: 90° (+/- 45°)

Monitor tilt range: 90° (+/- 45°)

Monitor tilt range: 90° (+/- 45°)

Monitor tilt range: 90° (+/- 45°)

Monitor tilt range: 90° (+/- 45°)

Monitor pan range: 180° (+/-90°)

Monitor pan range: 180° (+/-90°)

Monitor pan range: 180° (+/-90°)

Monitor pan range: 180° (+/-90°)

Monitor pan range: 180° (+/-90°)

Monitor rotation: 360°

Monitor rotation: 360°

Monitor rotation: 360°

Monitor rotation: 360°

Monitor rotation: 360°

Package dimensions: 19.4" x 7.6" x 5.9"

Package dimensions: 27.1" x 7.6" x 5.9"

Package dimensions: 32.4" x 7.6" x 5.9"

Package dimensions: 31.2" x 11.1" x 5.9"

Package dimensions: 31" x 14" x 5.9"

Arm weighs 7.8 lb with clamp, 6.5 lb with bolt-through

Weighs 10.2 lb with clamp, 9 lb with bolt-through

Arm weighs 9lb 13oz with clamp, 8lb 10oz with bolt-through

Arm weighs 9lb 13oz with clamp, 8lb 10oz with bolt-through

Arm weighs 9lb 13oz with clamp, 8lb 10oz with bolt-through

Bolt hole diameter: 0.4" to 3.1"

Bolt hole diameter: 0.4" to 3.1"

Bolt hole diameter: 0.4" to 3.1"

Bolt hole diameter: 0.4" to 3.1"

Bolt hole diameter: 0.4" to 3.1"

* With monitor at back of desk, max monitor width will decrease as the arms are pulled forward

** Height range measured from desk surface to center of monitor mount

*** Max forward reach measured from center of post to VESA plate

**** Side extension is how far the monitor arm can extend out to the left or right. It is measured from the center of the post/base to the center of the VESA plate